

TECHNICAL CHARACTERISTICS
AKCELA ACTIFULL OT CONCENTRATE
PRODUCT CODE: 1792

APPLICATION

Extended Life Coolant/Antifreeze concentrate, protective fluid. Based on ethylene glycol, organic corrosion inhibitors and bittering agent.

SPECIFICATIONS

MAT 3624, ASTM D 6210 Type 1-FF, CUMMINS CES 14603

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
ASPECT	--	--	CLEAR
COLOUR	--	--	YELLOW
DENSITY @ 15°C	ASTM D 5931	g/cm3	1,120 - 1,135
pH (dil. 50%)	ASTM D 1287	--	8
ALCALINITY RESERVE	ASTM D 1121	ml HCl 0,1N	6,5
BOILING POINT (dil. 50%)	ASTM D 1120	°C	108
FREEZING POINT (dil. 50%)	ASTM D 1177	°C	-38
FOAM @ 88°C	ASTM D 1881	cc	40
GLASSWARE CORROSION TEST	ASTM D 1384	--	PASS
HARD WATER COMPATIBILITY	FIAT 50537	--	PASS

All technical data is provided for reference only.