



PETRONAS

TECHNICAL CHARACTERISTICS

TUTELA TRANSMISSION MULTIAXLE

PRODUCT CODE: 1439

APPLICATION

Synthetic Transmission Oil. Specifically formulated to satisfy the most severe needs of moder Gearboxes and Hypoid Differentials.

SPECIFICATIONS

SAE 75W-85, API GL 5, FIAT 9.55550 CONTRACTUAL TECHNICAL REF. N°F426.E06

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
ASPECT	--	--	B&C
COLOUR	--	--	GREEN or BROWN (LIGHT)
DENSITY 15°C	ASTM D 4052	g/cm ³	0.867
VISCOSITA' @ 100°C	ASTM D 445	cSt	11.5
VISCOSITY @ 40°C	ASTM D 445	cSt	72
VISCOSITY INDEX	ASTM D 2270	--	160
VISCOSITY @ -40°C	ASTM D 2983	cPs	38000
POUR POINT	ASTM D 97	°C	<-45
FLASH POINT Cl. O. C.	ASTM D 92	°C	230
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

09/2017